

















Dimensioni delle chiavi per viti a norma

												
	Esagono	Impronta esagonale						Impronta Torx® (T) / Torx® Plus (TP)				Impronta Torx®
								Femmina				Maschio
Norma	UNI 5737/5739 DIN 931/933	DIN 912 ISO 4762	DIN 6912	DIN 7984	DIN 7991	UNI/ISO 7380	DIN 913/914 915/916	ISO 14580	ISO 7380	ISO 14581	DIN 34827 FL	ISO 4014 4017
												
M	Dimensione chiave (mm)							Grandezza chiave				
1,4	3	1,3					0,7					
1,6	3,2	1,5					0,7					
2	4	1,5					0,9		7	7		
2,5	5	2					1,3	8	8	8		
3	5,5	2,5			2	2	1,5	10	10	10	6	E4
3,5	6							10	10	10		
4	7	3	3	2,5	2,5	2,5	2	20	20	20	8	E5
5	8	4	4	3	3	3	2,5	25	25	25	10	E6
6	10	5	5	4	4	4	3	30	30	30	20	E8
7	11											
8	13	6	6	5	5	5	4	45	40	45	27	E10
10	17	8	8	7	6	6	5	50	50	50	30	E12
12	19	10	10	8	8	8	6	55	55	55	45	E14
14	22	12	12	10	10		6					E18
16	24	14	14	12	10	10	8	60	60	60	50	E20
18	27	14	14	12	12		10					
20	30	17	17	14	12		10					
22	32	17		14	14		12					
24	36	19		17	14		12					
27	41	19										
30	46	22										
33	50	24										
36	55	27										
39	60											
42	65	32										
45	70											
48	75	36										
52	80											
56	85	41										
60	90											
64	95	46										

Fattori di conversione di coppie di serraggio

COPPIA DI SERRAGGIO: fattori di conversione						
Valore dato in	Valore richiesto in					
	Ncm	Nm	Kgcm	Kgm	in.lbs	ft.lbs
Ncm	1	0,01	0,10197	0,00102	0,0885	0,00738
Nm	100	1	10,197	0,10197	8,850	0,7375
Kg	9,807	0,09807	1	0,01	0,868	0,0723
Kgm	980,7	9,807	100	1	86,80	7,233
in.lbs	11,299	0,11299	1,152	0,01152	1	0,0833
ft.lbs	135,59	1,3559	13,826	0,13826	12	1

Valore richiesto
= Valore dato
x fattore di
conversione